



Dimensions
Height 180mm · Width 143mm · Depth 74mm

The system consists of a wall mounted control panel and automatic solenoid. The system only requires a 240v supply. The solenoid is powered by the control panel and requires only a three core cable.

Operation

Turning the keyswitch will give gas immediately and this is indicated on the front of the panel.

Any of the external interfaces such as the fire alarm or extraction system being activated will switch the system off automatically.

A PROVEN METHOD FOR GAS ISOLATION AND EXTRACTION SYSTEM INTERLOCKING. THE GASGUARD MANUAL SYSTEM IS QUICK AND EASY TO INSTALL AND PROVIDES BASIC NON PROVING ISOLATION WHILE AT THE SAME TIME GIVING THE VERSATILITY OF INTERFACES PROVIDED WITH THE OTHER FLAMEFAST GASGUARD SYSTEMS SUCH AS REMOTE STOP, EXTRACTION SYSTEM INTERLOCK AND FIRE ALARM.

SYSTEM STANDARD FEATURES

Fire Alarm

The Gasguard system has a Fire Alarm interface fitted as standard.

Extraction Systems to BS6173

The system can easily be interfaced to a kitchen extraction system using a Flamefast differential pressure switch.

Emergency Stop Button

The panel includes an Emergency Stop Button and remote Emergency Stop Button Interface.

OPTIONAL EXTRAS

Actuator Enclosure

The actuator can be supplied fully enclosed and tamper proof if required.

Remote Emergency Stop Button

Additional Emergency Stops can be fitted remotely to the control panel to isolate the gas supply immediately in the event of an emergency.

Gas Sensor

Separate Natural Gas and LPG Sensors are available to isolate the gas supply immediately in the event of a gas leak during operation and give an audible and visual alarm.

Extraction Pressure Switch

Separate Extraction Pressure Switches are available if extraction pressure sensing is required.

◆ Please state actuator size when ordering ◆

FLAMEFAST (UK) LTD

Unit 2 · Labtec Street · Swinton · Manchester M27 8SE
Tel 0161 793 9998 · Fax 0161 793 0098
www.flamefast.co.uk · e-mail: sales@flamefast.co.uk